

Colt EXECUTIVE

ADVANCED ENGINEERED FOR
POWERFUL PERFORMANCE
AND EXCEPTIONAL STYLE

COLT EXECUTIVE

Bristling with high performance features like full suspension and a hydraulic sealed brake system the **Colt Executive** is a powerful blend of power and precision. The Colt Executive features sleek aggressive style and a wealth of standard luxury touches like a wraparound delta tiller and LED lighting, making it the ultimate outdoor scooter.



Colt Executive 140

Shown above with shield and pillow top
captains seat
(Images are for illustration purposes only)


Pride[®]
Mobility Products Ltd.
— LIVE YOUR BEST —

(Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pridemobility.co.uk

Colt Executive

Weight capacity:	181 kg (28.5 Stone)
Maximum speed ¹ :	Up to 12.87 km/h (8 mph)
Ground clearance ² :	13.33 cm (5.25")
Turning radius:	210.8 cm (83")
Overall length ² :	142.8 cm (56.25")
Overall width ² :	69.2 cm (27.25")
Front tyres:	10 cm x 33 cm (25" x 13") (pneumatic)
Rear tyres:	10 cm x 33 cm (25" x 13") (pneumatic)
Suspension:	Front and Rear
Maximum obstacle climbing ability:	12 cm (4.72")
Total Weight Without Batteries:	117.70 kg (259.5 lbs.)
Heaviest piece when disassembled:	Main frame: 93.21 kg (205.5 lbs.)
Standard seating:	Type: Pillow top captain style Weight: 21.77 kg (48 lbs.) Material: Black Vinyl Dimensions: width – 49.53 cm (19.5") (overall width) depth – 44.45 cm (17.5") (effective depth) height – 47 cm (18.5")
Drive System:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual Braking System:	Electronic, regenerative, and electromechanical
Battery Requirements ³ :	Two 12-volt, deep cycle Size: 75 AH (standard)/100 AH (optional) Weight ⁴ : 75 AH: 25 kg (55 lbs.) each; 100 AH: 27.44 kg (60.5 lbs.) each
Battery Charger:	8-amp, off-board

Colours:



Features

- Full suspension for optimum handling
- Sealed hydraulic brakes
- Large 33 cm (13") pneumatic tyres for excellent outdoor performance
- Full lighting package including directional signals and lower headlight
- Delta tiller with wraparound handles
- Easily accessible tie down points (for transport of unoccupied scooter)
- Rear view mirror standard
- Front shield standard

Options

- Double crutch holder
- Oxygen tank holder
- Rear basket
- Additional rear view mirror

¹Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition.

²Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³AGM or Gel-Cell type required.

⁴Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; due to the manufacturers commitment to constant improvement and development, they reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.