



Quantum® 610

POWER CHAIR

Q610 shown with Synergy® Seating System,
and PG VR2 controller



True All Around Performance.

The compact Quantum® 610 is the ultimate choice for users who demand the superb stability of Mid-Wheel 6® Design and tight-quarter manoeuvrability. Highly adaptable, the Quantum 610 accepts a wide range of seating and electronic options while its powerful drivetrain delivers high-performance torque.

(Images are for illustration purposes only)



Specifications

DRIVE WHEELS	25 cm (10")
OMNI-CASTORS	Front: 13 cm (5") solid Rear: 15 cm (6") solid
SUSPENSION	ATX Suspension (Active-Trac® with extra stability)
MAXIMUM SPEED ¹	Up to 6 km/h (4 mph)
BRAKES	Intelligent Braking (electronic, regenerative disc brakes)
GROUND CLEARANCE	6 cm (2.375")
TURNING RADIUS ²	54 cm (21.25")
OVERALL SIZE ²	Length: 88.25 cm (34.75") ³ Width: 59 cm (23.25")
SEATING	Synergy® Seat Adjustable Width: 25 cm - 51 cm (10"-20") Adjustable Depth: 25 cm - 51 cm (10"-20") TRU-Comfort® Seating Adjustable Width: 41 cm-56 cm (16"-22") Adjustable Depth: 41 cm-56 cm (16"-22") TRU-Balance® Power Positioning System Adjustable Width: 35.5 cm - 51 cm (14"-20") Adjustable Depth: 35.5 cm - 51 cm (14"-20")
DRIVE TRAIN	2-motor (Glide), Mid-Wheel 6®
BATTERIES	Two 12 volt, deep cycle, 30 AH
BATTERY CHARGER	5 amp, off-board (standard)
AVAILABLE ELECTRONICS	70 amp, PG VR2 (standard) 70 amp, Pilot Plus (optional)
WEIGHT CAPACITY	136 kg (21 Stone) maximum (user weight)
BASE WEIGHT	51 kg (112 lbs.)
BATTERY WEIGHT⁴	11 kg (24.5 lbs.) (each)
WARRANTY	Lifetime limited warranty on frame; 1-year limited warranty on electronics; 18-month warranty on drive control system; 2-year limited warranty on drive train

Colours



Metallic Red

Metallic Blue

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.

Features

- Mid-Wheel 6® allows six wheels on the ground for maximum stability
- Compatible with TRU-Balance® Power Positioning
- OMNI-Castors (nylon, spherical-shaped castors) on front and rear prevent wheel hang-ups
- Side-mounted, easily accessible freewheel levers
- ATX Suspension (Active-Trac® with extra stability) incorporates front OMNI-Castors for enhanced performance over more varied terrain
- Easy front access to batteries
- Powerful GLIDE motors for added power and torque
- 5A, Off-board charger

Options

- Synergy® seating system
- TRU-Comfort® seating system
- TRU-Balance® Power Positioning System
- Cup holder
- Oxygen bottle holder
- Crutch holder
- Rear basket
- Leg rest options (see script form)
- joystick mounts (see script form)
- Solid tyres

FOOTNOTES:

- 1) Range and speed vary with user weight, terrain type, battery charge, battery condition and tyre pressure.
- 2) Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3 %.
- 3) Without foot riggings
- 4) Battery weight may vary based on manufacturer